

TIRE-PATCH MB



Product descriptions

REF.No.	MODEL No.	SIZE(mm)	PLY	BOX QTY
28301	MB-01	60	1	30 pcs.
28302	MB-02	80	2	15 pcs.
28303	MB-03	91	2	10 pcs.
28304	MB-04	127	2	10 pcs.
28305 / 28405	MB / MS-05	165	4	10 pcs.
28306 / 28406	MB / MS-06	240	6	10 pcs.
28307 / 28407	MB / MS-07	295	6	10 pcs.
28308 / 28408	MB / MS-08	345	6	10 pcs.
28309 / 28409	MB / MS-09	390	8	10 pcs.
28310 / 28410	MB / MS-10	450	8	5 pcs.
28320	MB-20	255	4	10 pcs.
28321	MB-21	370	4	5 pcs.
28322	MB-22	510	4	5 pcs.

REF.No.	MODEL No.	SIZE(mm)	PLY	BOX QTY
28323	MB-23	255	6	10 pcs.
28324	MB-24	370	6	5 pcs.
28325	MB-25	510	6	3 pcs.
28330 / 28430	MB / MS-30	250	6	10 pcs.
28331 / 28431	MB / MS-31	350	6	10 pcs.
28332 / 28432	MB / MS-32	450	8	5 pcs.
28333 / 28433	MB / MS-33	550	8	5 pcs.
28334 / 28434	MB / MS-34	650	10	3 pcs.
28335 / 28435	MB / MS-35	750	12	3 pcs.
28340	MB-40	160	4	10 pcs.
28341	MB-41	235	6	10 pcs.
28342	MB-42	265	8	10 pcs.

Properties

- Can be used on all types of bias tires from passenger cars to heavy construction equipment.
- A wide variety of product types to repair any type or size of injury.
- Select a patch depending on the type and location of injury (MB for tread, MS for sidewall)
- Provides permanent repairs.
- Rubber is compounded to provide strength and to last longer. Also features a reinforcing inner layer composed of strong nylon fibers.
- The bonding and reinforcing layer are combined and will not separate.
- Can be cold cured (chemical self-vulcanizing) to enable quick and effective repairs.
- When cold cured, always use with SUPER VALKARN G / CFC FREE.
- Use with STEM and SEALINER / CFC FREE for more complete repairs.
- Can be hot cured as well. When hot curing, always use with THERMO LIQUID.

Application

Can be used on all types of bias tires from passenger cars to heavy construction equipment. This patch is developed to ensure safer, easier, more economical and durable repairs.