

# TIRE-PATCH MB



## Product descriptions

REF.No.	MODEL No.	SIZE(mm)	PLY	BOX QTY
28301	MB-01	60	1	30 pcs.
28302	MB-02	80	2	15 pcs.
28303	MB-03	91	2	10 pcs.
28304	MB-04	127	2	10 pcs.
28305 / 28405	MB / MS-05	165	4	10 pcs.
28306 / 28406	MB / MS-06	240	6	10 pcs.
28307 / 28407	MB / MS-07	295	6	10 pcs.
28308 / 28408	MB / MS-08	345	6	10 pcs.
28309 / 28409	MB / MS-09	390	8	10 pcs.
28310 / 28410	MB / MS-10	450	8	5 pcs.
28320	MB-20	255	4	10 pcs.
28321	MB-21	370	4	5 pcs.
28322	MB-22	510	4	5 pcs.

REF.No.	MODEL No.	SIZE(mm)	PLY	BOX QTY
28323	MB-23	255	6	10 pcs.
28324	MB-24	370	6	5 pcs.
28325	MB-25	510	6	3 pcs.
28330 / 28430	MB / MS-30	250	6	10 pcs.
28331 / 28431	MB / MS-31	350	6	10 pcs.
28332 / 28432	MB / MS-32	450	8	5 pcs.
28333 / 28433	MB / MS-33	550	8	5 pcs.
28334 / 28434	MB / MS-34	650	10	3 pcs.
28335 / 28435	MB / MS-35	750	12	3 pcs.
28340	MB-40	160	4	10 pcs.
28341	MB-41	235	6	10 pcs.
28342	MB-42	265	8	10 pcs.

## Properties

- Can be used on all types of bias tires from passenger cars to heavy construction equipment.
- A wide variety of product types to repair any type or size of injury.
- Select a patch depending on the type and location of injury (MB for tread, MS for sidewall)
- Provides permanent repairs.
- Rubber is compounded to provide strength and to last longer. Also features a reinforcing inner layer composed of strong nylon fibers.
- The bonding and reinforcing layer are combined and will not separate.
- Can be cold cured (chemical self-vulcanizing) to enable quick and effective repairs.
- When cold cured, always use with SUPER VALKARN G / CFC FREE.
- Use with STEM and SEALINER / CFC FREE for more complete repairs.
- Can be hot cured as well. When hot curing, always use with THERMO LIQUID.

## Application

Can be used on all types of bias tires from passenger cars to heavy construction equipment. This patch is developed to ensure safer, easier, more economical and durable repairs.